REFPRO
REFRIGERATION

R290

-18/-16°C

LED
lighting

Heated
double
glasses

REFPRO
REFRIGERATION

	MARIN TB 470	MARIN TB 340
Installation	Plug-in	Plug-in
Refrigeration	Statica; Ventilated	Statica; Ventilated
Outer Dimensions	670*740*1935 mm	520*740*1935 mm
Lighting	LED 5700 K	LED 5700 K
Operating Temperature	RV TB -18/-16 °C; RS TB -18 °C	RV TB -18/-16 °C; RS TB -18 °C
Refrigerant Gas	R290	R290
Defrost	Manual; Hot gas	Manual; Hot gas
Climate Class	7 (35 C° / 70% RH)	7 (35 C° / 70% RH)
Front Glass	Heated double glasses	Heated double glasses
Doors	1 door (1P)	1 door (1P)
Side Panels	Insulated white prepainted sheet	Insulated white prepainted sheet
Inside Color	White prepainted sheet	White prepainted sheet
Outer/Inner Body Color	White	White
Compressor	Hermetic	Hermetic
Shelves	7+1 bottom (RS); 5+1 bottom (RV) 542 x 392 mm	7+1 bottom (RS); 5+1 bottom (RV) 392 x 492 mm
Opening System	Door with automatic closure	Door with automatic closure
Equipment Handling	Rollers	Rollers